



C402G

Formerly LIN-324842-A

Fallstop® lanyard is designed to be used as a connecting device in a personal fall arrest, work positioning or travel restraint system. The lanyard connects the user's harness to an anchorage point, anchorage connector or a rope grab / fall arrester. Fallstop® rope lanyard is made of 5/8 in. (16 mm) diameter nylon rope that is manufactured using a heat set process that contributes to reduce the dynamic forces caused by a fall.

Features include:

- Provides better shock absorption than web lanyards.

Applicable standards:

- ANSI Z359.1
- ANSI A10.14
- OSHA fall protection requirements
- CSA approved models are available with forged components.

Applications:

- Fall arrest
- Work positioning
- Restraint

⚠WARNING The anchorage point location in combination with lanyard length should never permit a free fall distance of more than 6 feet (1.8 m). Consult local regulations as permitted free fall distance may be less than 6 feet.

⚠WARNING A 6-foot fall with a rope lanyard will generate an impact force up to 1,800 lbs. (8 kN), keep lanyard as short as possible to reduce risks of serious injury.

Available models:

C406G 6 ft. rope lanyard with a 3/4 in. double-locking snap hook at both ends

C406E 6 ft. rope lanyard with a 3/4 in. double-locking snap hook one end and a 2 1/4 in. double-locking snap hook at the other end

The rope lanyard is offered in lengths from 2 to 6 feet. To order a different length, replace the digit "6" in the code by the number corresponding at the desired length. i.e. C404G for a 4-foot rope lanyard.

For more information on the choice of connectors offered by Tractel, refer to technical sheet T-4536.

For further information refer to the "Use and Maintenance Instructions" for lanyards.

PARTS	SPECIFICATIONS	APPLICABLE STANDARDS
Rope	Nylon safety rope Diameter: 5/8 in. (16 mm) Tensile strength: 8,800 lbs. (39 kN)	ANSI Z359.1
Termination	Eye spliced Nylon thimble 1/2 in. (13 mm) Finished with shrink tubing	
3/4 in. double-locking snap hook	Constructed of die-cut steel, zinc plated Tensile strength: 5,000 lbs. (22 kN)	ANSI Z359.1
2 1/4 in. double-locking snap hook	Constructed of die-cut steel, zinc plated Tensile strength: 5,000 lbs. (22 kN)	ANSI Z359.1
Capacity	310 lbs. (140 Kg) One person	