Swing Staging
A SAFWAY Group Company
25-20 Borden Ave,
Long Island City,
NY 11101
(718) 361 2861

SKY RISE

Hydraulic Swing Hoist Series

An ASE ORIGINAL 2000 Single Line Swing Hoist

The HEAVIEST-DUTY SWING HOIST IN THE MARKET !

*Maximum capacity of 2,000 Lbs on a single line (with 200ft cable)
*Dependable Honda Engine
*Powerful Hydraulic System and fingertip control allow precision & ultra smooth load control
*The ONLY hoist in the market that can be set up to swing left or right (without extra pieces)
*Detached power unit with 10ft hoses permits the operator to control the hoist in the optimal position
*Safety system is backed by a double brake ensuring maximum protection
*Hoist frame breaks down into 8 pieces for maximum portability (fits in a freight elevator)
*5/16" hoist cable (meets OSHA requirements)

MODEL	2000 SINGLE	2000 DOUBLE	1500 DOUBLE
Gasoline Engine	20 H.P.	18 H.P.	13 H.P.
Honda Engine Model	GX620	GX610	GX390
Electric Start (Gasoline)	Standard	Standard	Optional
Electric Motor (3 Phase)	15 H.P.	10 H.P.	7.5 H.P.
Double Line Capacity with 200ft Cable	N/A	2000 lbs.	1500 lbs.
Single Line Capacity with 200ft Cable	2000 lbs.	1600 lbs.	1000 lbs.
Cable Capacity of Winch	500+ ft.	1000 ft.	1000 ft.
Cable Diameter	5/16"	1/4"	1/4"
Max. Lift Speed	200 fpm	160 fpm	160 fpm
Height of Swing	12 ft. 9 in	12 ft. 9 in	12 ft. 9 in
Reach of Swing	5 ft.	5 ft.	5 ft.
Shipping Weight	1250 lbs.	1250 lbs.	1200 lbs.

ELEVATE your EXPECTATIONS

Hand Winch

* The Hand Winch is an optional attachment for the Swing Hoist.
* Handy when hoist power pack & winch cannot be taken in elevator.

-standard with 120 ft. x 3/16 cable,,
-winch up or down,
-capacity:1000 lbs.
-EZ on / Ez Off

Ground Base

*Ground Base allows the power pack and winch to be operated at ground level.
*A cable block must be mounted on a beam above the lift area.

NOTE: COUNTERWEIGHTS MUST ALWAYS BE USED ON THE HYDRAULIC SWING HOIST WHEN LIFTING ANY KIND OF MATERIAL OR EQUIPMENT. APPROXIMATELY 1.5 TIMES THE WEIGHT BEING LIFTED IS RECOMMENDED.