

**NEW!**

# Miller® Lanyards & Self-Retracting Lifelines with Aluminum Connectors

*Lightweight • 3600-lb. rated gate • ANSI Z359 Compliant*

## Features/Benefits

- Up to 20% lighter than comparable steel connecting devices
- Compliant with applicable ANSI Z359 standards enhancing compliance and safety on the job site
- Corrosion-resistant for longer service life and increased versatility for various job applications
- Rated for 3,600-lb. gate strength that complies with the highest level of regulatory standards



Part No.	No. of Legs	Unit Connector	Lanyard End Connector	Weight
<b>Miller Manyard® II Shock-Absorbing Lanyards (6 ft)</b>				
216MAL-Z/6	1	Aluminum Snap Hook	Aluminum Snap Hook	2.49 lbs.
219MAL-Z/6	1	Aluminum Snap Hook	Aluminum Rebar Hook	3.22 lbs.
233MAL-Z/6	1	Choke-off Loop	Aluminum Snap Hook	2.04 lbs.
233MRAL-Z/6	1	Choke-off Loop	Aluminum Rebar Hook	2.77 lbs.



<b>Miller StretchStop® Lanyards w/ SofStop® Shock Absorber (6 ft)</b>				
913ALS-Z/6	1	Aluminum Snap Hook	Aluminum Snap Hook	1.32 lbs.
913RALS-Z/6	1	Aluminum Snap Hook	Aluminum Rebar Hook	2.24 lbs.
8798ALS-Z/6	2	Aluminum Snap Hook	Aluminum Snap Hooks	2.29 lbs.
8798RALS-Z/6	2	Aluminum Snap Hook	Aluminum Rebar Hooks	3.69 lbs.



<b>Miller HP™ Lanyards w/ SofStop® Shock Absorber (6 ft)</b>				
913TALS-Z/6	1	Aluminum Snap Hook	Aluminum Snap Hook	1.09 lbs.
922TRALS-Z/6	1	Aluminum Snap Hook	Aluminum Rebar Hook	1.84 lbs.
8798TALS-Z/6	2	Aluminum Snap Hook	Aluminum Snap Hooks	2.04 lbs.
8798TRALS-Z/6	2	Aluminum Snap Hook	Aluminum Rebar Hooks	3.44 lbs.



<b>Miller TurboLite™ Personal Fall Limiter (6 ft)</b>				
MFL-11-Z7/6FT	1	Aluminum Carabiner	Aluminum Snap Hook	2.0 lbs.
MFL-12-Z7/6FT	1	Aluminum Carabiner	Aluminum Rebar Hook	3.0 lbs.
MFL-14-Z7/6FT	1	Aluminum Snap Hook	Aluminum Snap Hook	2.3 lbs.
MFL-16-Z7/6FT	1	No unit connector	Aluminum Snap Hook	1.8 lbs.
MFL-17-Z7/6FT	1	No unit connector	Aluminum Rebar Hook	2.5 lbs.

Note: Locking Snap Hook - 3/4 inch (19mm) gate opening; Locking Rebar Hook - 2 1/2 inch (63mm) gate opening



Part No.	No. of Legs	Unit Connector	Lanyard End Connector	Weight
<b>Miller Twin Turbo™ Fall Protection System (6 ft)</b>				
MFLB-11-Z7/6FT	2	Twin Turbo D-Ring Connector	Aluminum Snap Hooks	4.5 lbs.
MFLB-12-Z7/6FT	2	Twin Turbo D-Ring Connector	Aluminum Rebar Hooks	6.0 lbs.



<b>Miller Scorpion™ Personal Fall Limiters (9 ft)</b>				
PFL-18-Z7/9FT	1	Aluminum Carabiner with Swivel Shackle	Aluminum Snap Hook	3.5 lbs.
PFL-19-Z7/9FT	1	Aluminum Rebar Hook with Swivel Shackle	Aluminum Snap Hook	4.0 lbs.
PFL-20-Z7/9FT	1	Aluminum Snap Hook with Swivel Shackle	Aluminum Snap Hook	3.7 lbs.
PFL-21-Z7/9FT	1	Aluminum Snap Hook with Swivel Shackle	Aluminum Rebar Hook	4.1 lbs.



<b>Miller MiniLite™ Fall Limiters (11 ft)</b>				
FL11-13-Z7/11FT	1	No unit connector	Aluminum Snap Hook	2.8 lbs.
FL11-14-Z7/11FT	1	Aluminum Carabiner	Aluminum Snap Hook	2.4 lbs.
FL11-15-Z7/11FT	1	Aluminum Rebar Hook with Swivel Shackle	Aluminum Snap Hook	2.7 lbs.
FL11-16-Z7/11FT	1	Aluminum Snap Hook with Swivel Shackle	Aluminum Snap Hook	3.4 lbs.



<b>Miller Falcon™ Self-Retracting Lifelines (16 and 20 ft)</b>				
MP16P-1-Z7/16FT	1	Aluminum Carabiner with Stainless Steel Swivel	Aluminum Snap Hook	3.0 lbs.
MP20P-1-Z7/20FT	1	Aluminum Carabiner with Stainless Steel Swivel	Aluminum Snap Hook	3.2 lbs.

*This equipment should only be used after reading the manufacturer's instructions. Failure to follow instructions could result in serious injury or fatality.*



by Honeywell



Ask the Expert ... Ask Miller.

800/873-5242

Fax 800/892-4078

[www.millerfallprotection.com](http://www.millerfallprotection.com)