

HydraPaks

HYDRAPAK GASOLINE

The RGC HydraPak is a powerful, portable hydraulic unit that operates more efficiently and with less noise than other types of power systems. Use one to operate RGC and other compatible hydraulic tools. Choose from a variety of models with variable flow and pressure settings. Or ask about the new HV1855 and operate two tools at once. These units are easily transported to your job site in the back of your pickup or van.

FEATURES

- Compact, lightweight hydraulic power source for RGC and other hydraulic tools
- Cart-mounted with large 16 in. pneumatic tires
- Low noise level
- Easy maintenance and parts replacement
- Electric start on all models
- Briggs & Stratton Vanguard gas engine with Performance Control™ electronic governor on the new HV1855, HV1810 and HV1858 (idle down control with delay feature eliminates speed fluctuation during intermittent use)
- Controls easily accessible for safety and comfort
- Strong, tubular steel frame protects unit from damage
- Detachable handles for easy transporting and storage
- Lifting eye and 6 gallon oil reservoir
- Heavy-duty 8-tube heat exchanger, 10-tube exchanger on HV1855



HV1855



HV1810XL Control Panel



HV1858 Control Panel

HV1810XL FEATURES

- Extra-wide deluxe tires for more stability on rough terrain
- Gauge kit includes engine hourmeter, voltmeter and pressure gauges for monitoring scheduled maintenance, battery power and hydraulic pressure

We reserve the right to make improvements at any time. Specifications and design are subject to change without notice

SPECIFICATIONS

Model	HH1358	HV1658	HV1855	HV1858	HV1810	HV1810XL
Engine	Honda 13 hp	B&S 16 hp Vanguard V-Twin	B&S 18 hp Vanguard V-Twin with Auto Idle	B&S 18 hp Vanguard V-Twin with Auto Idle	B&S 18 hp Vanguard V-Twin with Auto Idle	B&S 18 hp Vanguard V-Twin with Auto Idle
Fuel Capacity	7 qt (6.5 ltr)	9 qt (8.6 ltr)	9 qt (8.6 ltr)	9 qt (8.6 ltr)	9 qt (8.6 ltr)	9 qt (8.6 ltr)
Flow	5 or 8 gpm (20 or 30 lpm)	5 or 8 gpm (20 or 30 lpm)	5 gpm (20 lpm) [Powers 2 Tools]	5 or 8 gpm (20 or 30 lpm)	0-10 gpm (0-38 lpm)	0-10 gpm (0-38 lpm)
Pressure (Max)	2250 psi (155 bar)	2250 psi (155 bar)	2250 psi (155 bar)	2250 psi (155 bar)	1750 psi (120 bar) 2000 psi (138 bar) 2500 psi (172 bar)	1750 psi (120 bar) 2000 psi (138 bar) 2500 psi (172 bar)
Weight	240 lbs. (109 kg)	278 lbs. (126 kg)	295 lbs. (134 kg)	280 lbs. (127 kg)	287 lbs. (130 kg)	297 lbs. (135 kg)
Hourmeter	Yes	No	Yes	Yes	No	Yes



P.O. Box 681 • Buffalo, NY 14240-0681
 Phone: (716) 895-1156 • Fax: (716) 895-1547
 Toll free at **1-800-RGC-TOOL (742-8665)**
 or on the Internet at **www.rgcproducts.com**
 © 2000 Reimann & Georger Corp. All rights reserved.

HydraPak

HYDRAPAK ELECTRIC

The RGC HydraPak is a powerful, portable hydraulic unit that operates more efficiently and with less noise than other types of power systems.

Take it with you to any job site in the back of your pick-up or van, and use it to power all of your hydraulic tools. For more information, visit your RGC dealer or call the number below.

FEATURES

- 10 hp Baldor motor
- Compact, lightweight hydraulic power source for RGC and other hydraulic tools
- Strong, tubular steel frame protects unit from damage
- Controls easily accessible for safety and comfort
- Detachable handles for easy transporting and storage
- Lifting eye and 6 gallon oil reservoir

SPECIFICATIONS

Model	HE1058	HE1010
Motor	10 hp Baldor	10 hp Baldor
Voltage	208-230 v	208-230 v
Current	30 A	30 A
Phase	3	3
Flow	5 or 8 gpm (20 or 30 lpm)	0-10 gpm (0-38 lpm)
Pressure (Max)	2250 psi (155 bar)	1750 psi (120 bar) 2000 psi (138 bar) 2500 psi (172 bar)
Weight	280 lbs. (127 kg)	295 lbs. (134 kg)
Motor Starter	Optional	Standard



HE1010



Motor Starter



HE1010 Control Panel

OPTIONS

- Motor starters (HE1058)
- 460, 575 volt motors
- 50 hz motors

CH1355 HANDI PAK

The **new CH1355 Handi Pak** is a lightweight, compact, portable hydraulic power source ideal for work areas with limited space. Standard design includes a 13 hp Honda gas engine, dual filtration system, stainless steel protective frame, fold-down handle and wheels.

CH1355 SPECIFICATIONS

Model	CH1355
Engine	13 hp Honda
Flow	5 gpm (20 lpm)
Pressure (Max)	2000 psi (138 bar)
Weight	165 lbs. (75 kg)

We reserve the right to make improvements at any time.
Specifications and design are subject to change without notice



CH1355

RGC[®]
REIMANN & GEORGER CORP.
HOISTING - MARINE - CONSTRUCTION

P.O. Box 681 • Buffalo, NY 14240-0681
Phone: (716) 895-1156 • Fax: (716) 895-1547
Toll free at **1-800-RGC-TOOL (742-8665)**
or on the Internet at **www.rgcproducts.com**
© 2000 Reimann & Georger Corp. All rights reserved.

DISTRIBUTED BY: